

# Ampro MiniModule™ ISA PC/104-Plus Module

## Adds PC/104-Plus Expansion to PCI-104 SBCs



# MiniModule ISA

### Choose Ampro MiniModule ISA to...

Add PC/104-Plus expansion to ReadyBoard™ and CoreModule™ products that have a PCI-104 interface (PCI bus) or add PC/104-Plus, Compact Flash and Mini PCI capability.

### Description

Ampro's MM3-ISA-R-01 MiniModule ISA allows the hundreds of PC/104 modules to be used with SBCs that do not have PC/104 (ISA bus) support. MM3-ISA-R-11 adds more functionality to existing MM ISA by adding Compact Flash and Mini PCI dedicated sockets.



- Onboard PCI-to-ISA bridge
- CF and MiniPCI sockets
- Ampro BIOS supported
- Transparent to operating systems
- Full 24-bit ISA addressing
- 16-bit I/O and memory cycles

**For more information, pricing, and details on volume discounts, please call us at 1.800.966.5200 or +1.408.360.0200.** We'll immediately connect you to your local distributor.

We'll immediately connect you to your local distributor.

Don't see the product you need? Contact us at 1.800.966.5200 or +1.408.360.0200 for information about our semi-custom and custom solutions.

**Get Started Today. Order a QuickStart Kit Now.**

### Ordering Information

MODEL	DESCRIPTION
MM3-ISA-R-01	PCI-104 to PC/104-Plus bridge for RB 800
MM3-ISA-R-11	PCI-104 to PC/104-Plus bridge with CF and Mini PCI socket for RB 800 and CM 800

### Specifications

#### CONTROLLER

- ITE IT8888F PCI-to-ISA bridge
  - PCI 2.1 compliant
  - Transparent mode
  - Full 24-bit ISA addressing
  - 16-bit and 8-bit I/O and memory cycles
  - Software-transparent DMA
  - ISA bus master supports (4) PC/104 cards
  - Encodes all ISA IRQs

#### BUS INTERFACE

- PC/104-Plus (ISA & PCI) top side, PCI-104 bottom side (Q-01 only). Both connectors stack through for R-11 model.
- Compact Flash type II socket (R-11 only)
- Mini PCI type III socket for A/B (R-11 only)

#### SOFTWARE

- BIOS – Compatible with PCI-104 SBCs that use AMI BIOS with Ampro extensions

#### MECHANICAL

- Size – 90x96mm (3.6x3.8"); PC/104-Plus form-factor
- Power Requirements – TBD
- Operating temperature:
  - MM3-ISA-R-01: 0° to 60°C
  - MM3-ISA-R-11: –40° to +85°C



5215 Hellyer Ave., Ste. 110, San Jose, CA 95138 Tel. 408.360.0200 Fax 408.360.0222 sales@ampro.com

MAY.07

NOTICE: The product specifications provided in this datasheet are subject to change without notice. Every effort has been made to ensure the accuracy of this document. Ampro Computers, Inc., makes no warranties, expressed or implied, regarding errors or admissions and assumes no legal liability or responsibility for loss or damage resulting from the use of this document's information. ©2007 Ampro Computers, Inc. All rights reserved. Ampro is a registered trademark and CoreModule, LittleBoard, Little Board, MightyBoard, MightySystem, MiniModule, ReadyBoard, ReadyBox, ReadySystem, and RuffSystem, are trademarks of Ampro Computers, Inc. All other trademarks and registered trademarks are the property of their respective owners.

[www.ampro.com](http://www.ampro.com)