

Industrial Display Monitor

17" Stainless steel enclosure LCD Display

ADP-1176



Features

- 17" High Brightness TFT LCD display
- Stainless Steel enclosure
- IP 65 (water pfoof and anti-dust) on 5 sides, except I/O side
- VGA input (optional DVI,S-Video, RCA)
- Rear OSD keypad
- Touch Panel (optional)
- DC 11~28V wide-range power input
- Support VESA 75 mount



Display Specifications

Display	17" Color Active TFT Flat Panel Display
Luminance	300 cd/m ²
Viewing Angle	140/130 (H/V)
Resolutions	1280 x 1024 (native mode), 262K colors
Backlight Lifetime	50,000hrs
Touch Screen	Analog resistive (optional)
OSD Control	On the back side
I/O Connectors	1xDC power input, 1xVGA, optional:DVI,S-Video,RCA, touch (RS-232 or USB)
Power Input	DC 11~28V

Mechanical Specifications

Construction	Stainless Steel enclosure for IP 65 on 5 sides (except I/O side)
Dimensions	432 (W) x 358 (H) x 57.4(D)mm
Mounting	VESA 75

Environment Specifications

Operating Temperature	0~50°C(32~122°F)
Storage Temperature	-20~60°C (-4~140°F)
Relative Humidity	10~90% @40°C Non-condensing, without touch screen
Vibration	1G peak, 5~500 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)
Rating	NEMA 4/IP65 compliant front bezel
Certificate	Meet CE / FCC Class A

Optional Specifications

Black color of steel enclosure

Dimensions

