




Chassis Selection Guide

| Model No. | Type | Board Type | | Max. slots | Drive Capacity | | | | Fan Spec. | | | |
|------------|------|---------------------|--------------------------|------------|----------------|-----------|----------|----------|-----------|------|------|-------|
| | | Slot SBC | Motherboard | | 5.25" F.P. | 3.5" F.P. | 2.5" Int | 3.5" Int | 4 cm | 6 cm | 8 cm | 12 cm |
| RACK-1150G | 1U | PICMG 1.0 full-size | | 3 | 1 | | | 1 | 3 | | | |
| RACK-1151G | 1U | PICMG 1.0 full-size | | 3 | 1 | | | 1 | 3 | | | |
| RACK-220G | 2U | PICMG 1.0 full-size | *MicroATX, Mini-ITX | 6 | 1 | 1 | | 1 | | | 2 | |
| RACK-221G | 2U | PICMG 1.3 full-size | | 6 | 1 | 1 | | 1 | | | 2 | |
| RACK-2000G | 2U | PICMG 1.0 full-size | | 6 | 1 | 1 | | 1 | | | 2 | |
| RACK-2100G | 2U | PICMG 1.3 full-size | | 6 | 1 | 1 | | 1 | | | 2 | |
| RACK-1350G | 3U | | ATX, MicroATX, Mini-ITX | 7 | 2 | 1 | | 1 | | **2 | 2 | |
| RACK-3400G | 4U | half-size | | 10 | 2 | 1 | | | | | 2 | |
| RACK-305G | 4U | full-size | *ATX, MicroATX, Mini-ITX | 14 | 2 | 1 | | 1 | | ***2 | 2 | |
| RACK-360G | 4U | full-size | *ATX, MicroATX, Mini-ITX | 14 | 2 | 1 | | 1 | | ***2 | | 1 |
| RACK-814G | 4U | full-size | | 14 | 1 | 1 | | 1 | | | 3 | |
| RACK-3000G | 4U | full-size | *ATX, MicroATX, Mini-ITX | 14 | 3 | 2 | | 1 | | ***2 | 2 | |
| RACK-3200G | 4U | full-size | | 20 | +6 | 1 | | | | | 4 | |
| RACK-500G | 5U | full-size | | 5 | | 1 | | 1 | | | 1 | |
| RACK-900G | 5U | PICMG 1.0 full-size | | 10 | 1 | 1 | | 1 | | | 2 | |
| RACK-3035G | 7U | full-size | | 20 | +6 | | | | | | 5 | |
| PAC-42GF | | full-size | | 4 | | 1 | ▲2 | | | | 1 | |
| PAC-1000G | | full-size | | 6 | 1 | 1 | | 1 | | | 1 | |
| PAC-106G | | full-size | | 6 | | 1 | | 1 | | | 1 | |
| PAC-107G | | full-size | | 6 | 1 | 1 | | 1 | | | 1 | |
| PAC-1700G | | full-size | | 7 | 1 | 1 | | 2 | | | 1 | |
| PAC-125G | | full-size | | 10 | 2 | 1 | | 1 | | | 1 | |
| PAC-130G | | full-size | *MicroATX, Mini-ITX | 10 | 2 | 1 | | | | | 2 | |
| PAC-53GH | | half-size | | 3 | | | 1 | | | | | |
| PAC-54GH | | PICO/PICOe | | 3 | | | 1 | | | 1 | | |
| PR-1300G | | half-size | | 3 | | 1 | | | | 1 | | |
| PAC-42GH | | half-size | | 4 | | △1 | | △1 | | | 1 | |
| PACO-504H | | half-size | | 4 | | | | 2 | | | | |
| PR-1500G | | half-size | | 5 | ◇1 | 1 | | 1 | | | 1 | |
| PAC-400G | | half-size | | 5 | | | | △1 | | | 1 | |
| PAC-52G | | half-size | | 6 | | | | | | | | |
| PACO-506H | | half-size | | 6 | | | | 2 | | | | |
| PAC-700G | | half-size | | 7 | 1 | △1 | | 1 | | | 1 | |

 Rackmount chassis
 Full-size wall mount chassis
 Half-size wall mount chassis

* for ATX model
 ** optional
 *** optional fans for ATX model

◇ slim-type CD-ROM
 △ Please refer to datasheet for detail information
 † Each 5.25" space can be changed to 3.5"(F.P. or HDD) with optional bracket
 ▲ PAC-42GF can accommodate 2 x 2.5"HDD or 2 x 3.5" HDD

Chassis Selection Guide

| Indicators | | Front Panel Control | | | | | PSU | Dimensions(mm) | | | Color | | |
|------------|-----|---------------------|-------|--------------|-----|---------|------------------------|----------------|--------|-------|-------|-------|-------|
| Power | HDD | Power | Reset | KB connector | USB | Keylock | | Depth | Height | Width | Black | White | Other |
| X | X | X | X | | 2 | | 1U | 449 | 44 | 431 | X | | |
| X | X | X | X | | 2 | | 1U | 440 | 44 | 431 | X | | |
| X | X | X | X | | 2 | X | PS/2 | 487.5 | 88 | 431 | X | X | |
| X | X | X | X | | 2 | X | PS/2 | 487.5 | 88 | 431 | X | X | |
| X | X | X | X | | | X | PS/2, redundant | 576.9 | 88 | 431 | X | X | |
| X | X | X | X | | 2 | X | PS/2, redundant | 576.9 | 88 | 431 | X | X | |
| X | X | X | X | | 2 | X | 2U | 480 | 133 | 431 | X | | |
| X | X | X | X | | | X | PS/2 or mini redundant | 283 | 176 | 431 | X | X | |
| X | X | X | X | X | 2 | X | PS/2 or mini redundant | 413 | 176 | 431 | X | X | |
| X | X | X | X | X | 2 | X | PS/2 or mini redundant | 435.5 | 176 | 431 | X | X | |
| X | X | X | X | | 2 | X | PS/2 or mini redundant | 454.7 | 176 | 431 | X | | |
| X | X | X | X | | | X | PS/2 or mini redundant | 520 | 176 | 431 | X | X | |
| X | X | X | X | | | X | PS/2 or mini redundant | 674 | 176 | 431 | X | X | |
| X | X | X | X | | 2 | | 1U | 440.2 | 221.3 | 110.6 | X | X | |
| X | X | X | X | | 2 | | 1U | 440.2 | 221 | 221 | X | | |
| X | X | X | X | | 2 | X | 2 x PS/2 redundant | 504 | 311 | 431 | X | | |
| X | X | X | X | | 2 | | 1U | 405 | 200 | 140 | | X | |
| X | X | X | X | | | | PS/2 | 421 | 176 | 232 | X | | |
| X | X | X | X | | 2 | | 1U | 400 | 175.5 | 166 | | X | |
| X | X | X | X | | 2 | | 1U | 400 | 218.5 | 166 | | X | |
| X | X | X | X | | | | PS/2 | 433 | 253.7 | 192.4 | X | | |
| X | X | X | X | | 2 | X | PS/2 | 420 | 176 | 321 | | X | |
| X | X | X | X | | 2 | | PS/2 | 350 | 176 | 350 | X | | |
| X | X | X | X | | 2 | | 1U | 218 | 200 | 95 | | X | |
| X | X | X | X | | 2 | | 1U | 253 | 200 | 95 | | X | |
| X | X | X | X | | 2 | | 1U | 254 | 88 | 265 | | X | |
| X | X | X | X | | 2 | | 1U | 269 | 230 | 140 | | X | |
| | | | | | | | N/A | 362 | 124 | 158 | | | |
| X | X | X | X | | 2 | | 1U | 254 | 132 | 286 | | X | |
| X | X | X | X | | 2 | | 1U | 269 | 230.5 | 140 | | X | |
| X | | | X | | 1 | | N/A | 218 | 147 | 152.2 | | X | |
| | | | | | | | N/A | 226 | 157 | 170 | | | |
| X | X | X | X | | 2 | X | 1U | 279 | 176 | 321 | X | | |

1

Industrial
Computing
Solutions

2

Embedded
Computing
Solutions

3

RISC-Based
Embedded
Solutions

4

Industrial
Data
Collector/
Server
Solutions

5

Video
Capture
Solutions

6

I/O
Communication
Solutions

7

Panel
Solutions

8

Power Supply/
Network
Communication/
Peripherals