

















Micro Commercial Components Corp.

Surface Mount Zener Diodes Selection Guide

Part Numbers	Package Types	Zener Voltage(V)	Power Rating (W)
BZT52C2V4T~BZT52C39T	 SOD-523	2.4~39	0.1
BZT52C2V4S~BZT52C39S	 SOD-323	2.4~39	0.2
MMXZ5221B~MMXZ5259B		2.4~39	0.2
MMSZ5221B~MMSZ5259B	 SOD-123	2.4~39	0.5
BZT52C2V4~BZT52C39		2.4~39	0.5
BZX84C2V4W~BZX84C39W	 SOT-323	2.4~39	0.2
MMBZ5221BW~MMBZ5259BW		2.4~39	0.2
BZX84C2V4~BZX84C39	 SOT-23	2.4~39	0.35
MMBZ5221B~MMBZ5259B		2.4~39	0.35
BZM55C2V0~BZM55C75	 MICROMELF	2.0~75	0.5
MCL5221B~MCL5276B		2.4~150	0.5
BZV55C2V0~BZV55C75	 MINIMELF	2.0~75	0.5
DL5221B~DL5276B		2.4~150	0.5
DL5518B~DL5546B		3.3~33	0.5
DLZ3.6B~DLZ39B		3.60~37.19	0.5
LLZ2V4~LLZ56		2.33~60.0	0.5
MLL746A~MLL759A		3.3~12.0	0.5
LSH2A3~LSH36		 QUADROMELF	1.8~38.0
DL4728A~DL4764A	 MELF	3.3~100	1
SMAJ4728A~SMAJ4764A	 SMA	3.3~100	1
SMAJ5918B~SMAJ5942B		5.1~51	1.5
SMAZ5V1~SMAZ39		5.1~39	1
SMBJ5338B~SMBJ5369B	 SMB	5.1~51	5
SMBJ5918B~SMBJ5942B		5.1~51	1.5
3SMBJ5918B~3SMBJ5942B		5.1~51	3

Note : Standard VZ tolerance is $\pm 5\%$, other tolerances available upon request.

Micro Commercial Components Corp. Axial Lead Zener Diodes Selection Guide

Part Numbers	Package Types	Zener Voltage(V)	Power Rating (W)	
MTZJ2.0A~MTZJ39D	 DO-34	1.88~38.52	0.5	
H2A3~H36	 DO-35	1.8~38	0.5	
1N5221B~1N5276B		2.4~150	0.5	
1N4614~1N4125		1.8~47	0.5	
1N4678~1N4713		1.8~30	0.5	
1N5985B~1N6016B		2.4~47	0.5	
1N746A~1N759A		3.3~12	0.5	
1N957B~1N982B		6.8~75	0.5	
BZX55C2V0~BZX55C75		2.0~75	0.5	
BZX79C2V4~BZX79C75		2.4~75	0.5	
1N4728A~1N4764A		 DO-41G	3.3~100	1
1N5918B~1N5942B			5.1~51	1.5
BZX85C2V7~BZX85C75	2.7~75		1.3	
ERD2.0FB~ERD75FB	2.0~75		1	
1EZ110D5~1EZ200D5	 DO-41	110~200	1	
2EZ11D5~2EZ75D5		11~75	2	
ZPY5.1~ZPY51		5.1~51	1.3	
ZY5.1~ZY51		5.1~51	2	
3EZ11D5~3EZ39D5	 DO-15	11~39	3	
1N5338B~1N5369B		5.1~51	5	

Note : Standard VZ tolerance is $\pm 5\%$, other tolerances available upon request.